BANNER & VINYL

PRODUCT DATA SHEET

Rev 3 - Updated 8/18

900 15 MIL SCRIM VINYL BANNER -MATTE

PRINTER COMPATIBILITY



*For additional information visit www.dietzgen.com *Does not guarantee optimal performance

PROCESSING TIPS

- Preferred side out

FINISHING & PRINTING

- Allow sufficient time for prints to completely dry before rolling, laminating or cutting.
- Use a sharp blade to prevent ink and toner flaking on the edges
- Compatible with most brands of banner tape
- Compatible with most brands of grommets
- Grommets should be placed in multiple layers in th hemline (reinforced corners are also recommended)

SHELF LIFE

2 years from ship date

STORAGE CONDITIONS

 Temperature
 70° F (21° C)

 Relative Humidity
 50%

 Temperature
 50-85° F (10-30° C)

 Relative Humidity
 30-65%

OPTIMAL SERVICE ENVIRONMENT

Temperature	50-85° F (10-30° C)
Relative Humidity	30-65%

DESCRIPTION

900 is a high quality 15 mil, brite white, tear and scratch resistant, scrim vinyl banner with a waterproof matte coating.
900 is constructed of tear resistant polyester fabric sandwiched between two layers of white vinyl.
900 provides excellent ink adhesion, print quality, black density, color pop and image clarity as well as exceptional strengh and durability for repeated handling. Short term outdoor.

PHYSICAL CHARACTERISTICS

Caliper	15 mil
Basis Weight	445 g/m²
Brightness	NA
Opacity	85%
Finish	Matte
Whiteness	120
Smoothness	NA
Lab Values	NA
Base material	Scrim Vinyl
Structure	Coated
*All values are for reference only	

FEATURES AND BENEFITS

- Smooth, durable, scrim banner vinyl
- Good tear resistance
- Excellent print performance
- Excellent ink adhesion
- Excellent black density and color pop
- Water / fade / scratch resistant coating
- Smooth matte finish
- Short term outdoor durable
- Grommeting and welding

121 Kelsey Lane | Suite G | Tampa, Florida 33619 800-854-2341 | customerservice@dietzgen.com my.dietzgen.com | © Dietzgen Corporation

